

Woodura Planks 3.0

GULLARP 3.0 XXL

Type of wood
AshGrading
SelectSurface finishing
Pro matt lacquerStaining
Powder WhitePattern
PlankWater resistance
High

Gullarp er et hvidt, matlakeret gulv i hærde asketræ med et frisk udtryk. Denne skandinaviske klassiker i den lyse nuance Powder White i kombination med sorteringen Select giver gulvet et rent og harmonisk udseende. Gullarp er et klasse 33-produkt, hvilket betyder, at det er ekstremt slidstærkt og passer perfekt til rum med meget gangtrafik såsom hoteller, butikker, kontorer og caféer – eller entréen i dit hjem. Den matlakerede finish gør gulvet nemt at vedligeholde og beskytter samtidig mod pletter.



Specification

GENERAL

Type of floor	Hardened wood
Type of wood	Ash
Grading	Select
Surface finishing	Pro matt lacquer
Staining	Powder White
Light/dark	Light
Pattern	Plank
Locking system	Välinge 5G® Dry™
Core	HDF

DIMENSIONS

Format	XXL
Width	271 mm
Length	2378 mm
Thickness	11 mm
Thickness of wear layer	0,6 mm

PACKAGE

Quantity in box	3 pcs
m² / box	1,9 m²
m² per pallet	93 m²
Weight per m²	11 kg
Weight per box	22 kg

CLASSIFICATION AND SAFETY

Supports Underfloor Heating	Yes
Water resistance	High
Fire Resistance (EN 13501)	Cfl-s1
Thermal conductivity (EN 12664)	0,16 W/(m*K)
Thermal resistance (EN 12667)	0,07 m²K/W
Formaldehyde emission (EN 717-1)	E1 <=0,1 ppm (typical value <= 0,05 ppm)
Brinell hardness (EN 1534)	10 HB (average value)
Impact resistance (EN 14354)	EC3
Thickness swelling (EN 14354)	<10% (5% typical)
Wear resistance (EN 14354)	> 6000 cycles
Slip resistance (USRV) (CEN//TS 15676)	40
FSC	FSC Mix (FSC-C140725)
Svanen	Yes (3029 0021)
Greenguard Gold	Greenguard Gold Certified
CE Marked	Yes
Limited warranty (public environment)	30 years
Limited warranty (home environment)	30 years
Level of use domestic (EN ISO 10874)	Class heavy Residential (Class 23)
Level of use commercial (EN ISO 10874)	Class heavy commercial (Class 33)



woodura®

Bjelin Sweden AB | bjelin.com | sales@bjelin.com | +46-771-101 099

Copyright 2025 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



For installation and caring instructions, and further product information, scan the QR code or visit bjelin.com.