

Hardened Wood 2.5

WOODURA PLANKS SMEDSTORP
XXL EARTH GREY 2.5



Type of wood
Ash



Grading
Select



Surface finishing
Matte finish



Staining
Earth Grey



Pattern
Plank



Water resistance
High

Smedstorp is a toned-down hardened wood floor made from ash. Effortless and stylish, this floor in the Earth Grey color has been paired with the Select grading to provide a clean and harmonious appearance. Smedstorp is a class 31 product, which is ideal for residential areas. The matte finish makes the floor easy to maintain while protecting it from stains.

Specification

GENERAL

Type of floor	Hardened wood
Type of wood	Ash
Grading	Select
Surface finishing	Matte finish
Staining	Earth Grey
Light/dark	Light
Pattern	Plank
Locking system	Välinge 5G® Dry™
Core	HDF
Level of use	Residential

DIMENSIONS

Format	XXL
Width (ISO 24337)	10.7"
Length (ISO 24337)	93.6"
Thickness (ASTM F387)	0.43"
Thickness of wear layer (ASTM F410)	0.02"
Weight per m²	999 sqft

PACKAGE

Quantity in box	3 pcs
sq.ft per box	20.81 sqft
sq.ft per pallet	999 sqft
Weight per box	47.8 lbs

CLASSIFICATION AND SAFETY

Supports Underfloor Heating	Yes
Water resistance	High
Fire Resistance (EN 13501)	Cfl-s1
Thermal conductivity (EN 12664)	0,16 W/(m*K)
Thermal resistance (EN 12667)	0.07 m²K/W
Formaldehyde emission (EN 717-1)	E1 <=0.1 ppm (typical value <= 0.05 ppm)
Brinell hardness (EN 1534)	10 HB (average value)
Impact resistance (EN 14354)	EC3
Thickness swelling (EN 14354)	<10% (5% typical)
Wear resistance (EN 14354)	> 6000 cycles
Slip resistance (USRV) (CEN//TS 15676)	40
FSC	FSC Mix (FSC-C140725)
Greenguard Gold	Greenguard Gold Certified
CE Marked	Yes
Warranty (commercial)	10 years
Warranty (residential)	Limited Lifetime Warranty
Level of use domestic (EN ISO 10874)	Class heavy Residential (Class 23)
Level of use commercial (EN ISO 10874)	Class light commercial (Class 31)



woodura®

Bjelin bjelin.com us-support@bjelin.com

Copyright 2025 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



For installation and caring instructions, and further product information, scan the QR code or visit bjelin.com.