

## Herringbone Parquet

## HERRINGBONE PARQUET SIGTUNA











Pattern Surfac

Staining Misty White

Sigtuna is a matt-lacquered herringbone floor that provides a stylish impression. The three-layer parquet in the popular Misty White is light, while the Select grading lends the floor a clean and harmonious look.



## **Specification**

Type of floor 3-layer parquet Type of wood Oak Grading Select Pattern Herringbone Surface finishing Matt lacquer Staining Misty White Light/dark Light Core HDF Locking system Välinge 5G® Bevel None  DIMENSIONS Thickness of wear layer 2,6 mm Length 345 mm Width 69 mm Thickness 14,6 mm	GENERAL	
Grading Select Pattern Herringbone Surface finishing Matt lacquer Staining Misty White Light/dark Light Core HDF Locking system Välinge 5G® Bevel None  DIMENSIONS Thickness of wear layer 2,6 mm Length 345 mm Width 69 mm	Type of floor	3-layer parquet
Pattern Herringbone Surface finishing Matt lacquer Staining Misty White Light/dark Light Core HDF Locking system Välinge 5G® Bevel None  DIMENSIONS Thickness of wear layer 2,6 mm Length 345 mm Width 69 mm	Type of wood	Oak
Surface finishing  Staining  Misty White Light/dark  Light Core  HDF Locking system  Välinge 5G® Bevel  None  DIMENSIONS  Thickness of wear layer  Length  345 mm  Width  69 mm	Grading	Select
Staining Misty White Light/dark Light Core HDF Locking system Välinge 5G® Bevel None  DIMENSIONS Thickness of wear layer 2,6 mm Length 345 mm Width 69 mm	Pattern	Herringbone
Light/dark Light Core HDF Locking system Välinge 5G® Bevel None  DIMENSIONS Thickness of wear layer 2,6 mm Length 345 mm Width 69 mm	Surface finishing	Matt lacquer
Core HDF Locking system Välinge 5G® Bevel None  DIMENSIONS Thickness of wear layer 2,6 mm Length 345 mm Width 69 mm	Staining	Misty White
Locking system Välinge 5G® Bevel None  DIMENSIONS  Thickness of wear layer 2,6 mm  Length 345 mm  Width 69 mm	Light/dark	Light
Bevel None  DIMENSIONS  Thickness of wear layer 2,6 mm  Length 345 mm  Width 69 mm	Core	HDF
DIMENSIONS Thickness of wear layer 2,6 mm Length 345 mm Width 69 mm	Locking system	Välinge 5G®
Thickness of wear layer 2,6 mm Length 345 mm Width 69 mm	Bevel	None
Thickness of wear layer 2,6 mm Length 345 mm Width 69 mm		
Length 345 mm Width 69 mm	DIMENSIONS	
Width 69 mm	Thickness of wear layer	2,6 mm
	Length	345 mm
Thickness 14,6 mm	Width	69 mm
	Thickness	14,6 mm

PACKAGE	
Quantity in box	38 pcs
m² / box	0,9046 m <sup>2</sup>
Weight per box	11 kg
CLASSIFICATION AND SAFETY	
FSC	FSC Mix (SA-COC-006371)
SundaHus	Evaluated by SundaHus
CE Marked	Yes
Limited warranty	20 years
Light Reflection Value (LRV)	36,9
Svanen	No
Supports Underfloor Heating	Yes
MISC.	
Nobb-nummer	56631154



