

# Herringbone Parquet

## HERRINGBONE PARQUET KALMAR



Kalmar is a sophisticated, matt-lacquered herringbone floor that complements soft shades. The three-layer parquet in Earth Grey is subtle and elegant, while the Select grading lends the floor a clean and harmonious look.



### Specification

| GENERAL                 |                 |
|-------------------------|-----------------|
| Type of floor           | 3-layer parquet |
| Type of wood            | Oak             |
| Grading                 | Select          |
| Pattern                 | Herringbone     |
| Surface finishing       | Matt lacquer    |
| Staining                | Earth Grey      |
| Light/dark              | Medium dark     |
| Core                    | HDF             |
| Locking system          | Välinge 5G®     |
| Bevel                   | None            |
| DIMENSIONS              |                 |
| Thickness of wear layer | 2,6 mm          |
| Length                  | 345 mm          |
| Width                   | 69 mm           |
| Thickness               | 14,6 mm         |

| PACKAGE         |           |
|-----------------|-----------|
| Quantity in box | 38 pcs    |
| m² / box        | 0,9046 m² |
| Weight per box  | 11 kg     |

| CLASSIFICATION AND SAFETY    |                                 |
|------------------------------|---------------------------------|
| FSC                          | FSC Mix Credit (DNV-COC-001624) |
| SundaHus                     | Evaluated by SundaHus           |
| CE Marked                    | Yes                             |
| Limited warranty             | 20 years                        |
| Light Reflection Value (LRV) | 26,2                            |
| Svanen                       | No                              |
| Supports Underfloor Heating  | Yes                             |



**Bjelin**   [bjelin.com](http://bjelin.com)   [uk-sales@bjelin.com](mailto:uk-sales@bjelin.com)

Copyright 2024 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB ([www.valinge.se/patents](http://www.valinge.se/patents)). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



For installation and caring instructions, and further product information, scan the QR code or visit [bjelin.com](http://bjelin.com).