

Herringbone Parquet HERRINGBONE PARQUET FALUN











n Surface finishing one Matt lacquer

Staining Shadow Brow

Falun is a beautiful, matt-lacquered herringbone floor in a lush brown shade. The three-layer parquet in Shadow Brown is sophisticated and warm while the Select grading lends the floor a clean and harmonious look.



Specification

Type of floor 3-layer parquet Type of wood Oak Grading Select Pattern Herringbone Surface finishing Matt lacquer Staining Shadow Brown Light/dark Dark Core HDF Locking system Välinge 5G® Bevel None DIMENSIONS Thickness of wear layer 2,6 mm Length 345 mm Width 69 mm Thickness 14,6 mm	GENERAL	
Grading Select Pattern Herringbone Surface finishing Matt lacquer Staining Shadow Brown Light/dark Dark Core HDF Locking system Välinge 5G® Bevel None DIMENSIONS Thickness of wear layer 2,6 mm Length 345 mm Width 69 mm	Type of floor	3-layer parquet
Pattern Herringbone Surface finishing Matt lacquer Staining Shadow Brown Light/dark Dark Core HDF Locking system Välinge 5G® Bevel None DIMENSIONS Thickness of wear layer 2,6 mm Length 345 mm Width 69 mm	Type of wood	Oak
Surface finishing Staining Shadow Brown Light/dark Dark Core HDF Locking system Välinge 5G® Bevel None DIMENSIONS Thickness of wear layer Length Width Matt lacquer 2,6 mm 345 mm Width 69 mm	Grading	Select
StainingShadow BrownLight/darkDarkCoreHDFLocking systemVälinge 5G®BevelNoneDIMENSIONSThickness of wear layer2,6 mmLength345 mmWidth69 mm	Pattern	Herringbone
Light/dark Dark Core HDF Locking system Välinge 5G® Bevel None DIMENSIONS Thickness of wear layer 2,6 mm Length 345 mm Width 69 mm	Surface finishing	Matt lacquer
CoreHDFLocking systemVälinge 5G®BevelNoneDIMENSIONSThickness of wear layer2,6 mmLength345 mmWidth69 mm	Staining	Shadow Brown
Locking system Välinge 5G® Bevel None DIMENSIONS Thickness of wear layer 2,6 mm Length 345 mm Width 69 mm	Light/dark	Dark
Bevel None DIMENSIONS Thickness of wear layer 2,6 mm Length 345 mm Width 69 mm	Core	HDF
DIMENSIONS Thickness of wear layer Length 345 mm Width 69 mm	Locking system	Välinge 5G®
Thickness of wear layer 2,6 mm Length 345 mm Width 69 mm	Bevel	None
Thickness of wear layer 2,6 mm Length 345 mm Width 69 mm		
Length 345 mm Width 69 mm	DIMENSIONS	
Width 69 mm	Thickness of wear layer	2,6 mm
	Length	345 mm
Thickness 14,6 mm	Width	69 mm
	Thickness	14,6 mm

PACKAGE	
Quantity in box	38 pcs
m² / box	0,9046 m²
Weight per box	11 kg
Boxes per pallet	96
m² per pallet	86,8416
Weight per pallet	960 kg
CLASSIFICATION AND SAFETY	
FSC	FSC Mix Credit (DNV-COC-001624)
FSC SundaHus	FSC Mix Credit (DNV-COC-001624) Evaluated by SundaHus
	·
SundaHus	Evaluated by SundaHus
SundaHus CE Marked	Evaluated by SundaHus Yes
SundaHus CE Marked Limited warranty	Evaluated by SundaHus Yes 20 years
SundaHus CE Marked Limited warranty Light Reflection Value (LRV)	Evaluated by SundaHus Yes 20 years 10,2
SundaHus CE Marked Limited warranty Light Reflection Value (LRV) Svanen	Evaluated by SundaHus Yes 20 years 10,2 No
SundaHus CE Marked Limited warranty Light Reflection Value (LRV) Svanen	Evaluated by SundaHus Yes 20 years 10,2 No



