

Nadura Tiles

CERAMIC COMPOSITE POLLUX



Specification

GENERAL	
Type of floor	Nadura Tiles
Locking system	Välinge 5G®
Core	HDF
Bevel	Decorative groove
DIMENSIONS	
Length	584 mm
Width	283 mm
Thickness	10,5 mm
PACKAGE	
Quantity in box	8 pcs
m² / box	1,32 m²
Weight per box	13,2

CLASSIFICATION AND SAFETY	
Limited warranty	20 years
Light Reflection Value (LRV)	23,1 ± 0,30
Svanen	Yes (3029 0021)
SundaHus	Evaluated by SundaHus
FSC	No
CE Marked	Yes
Supports Underfloor Heating	Yes
MISC.	
Wear class	AC 6
Classification EN 685	Class 34
Surface texture	Slate



Bjelin Sweden AB bjelin.com support@bjelin.se +46-771-101099

Copyright 2025 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.



For installation and caring instructions, and further product information, scan the QR code or visit bjelin.com.