

Nadura Tiles

Specification

GENERAL	
Type of floor	Nadura Tiles
Pattern	Tile
Locking system	Välinge 5G® Dry™
Core	HDF
Colour	Eclipse Grey Storm Grey Dew Grey
Bevel	Decorative groove
DIMENSIONS	
Width	280 mm
Width (ISO 24337)	11"
Length	582 mm
Length (ISO 24337)	22.9"
Thickness	10.5 mm
Thickness (ASTM F387)	0.41"
Thickness of wear layer	0.4 mm
Thickness of wear layer (ASTM F410)	.01"
Weight per m²	22 lbs
PACKAGE	
Quantity in box	8 pcs
m² / box	1.3 m²
sq.ft per box	13.99 sq.ft
m² per pallet	70.4 m²
sq.ft per pallet	758 sq.ft
Weight per m²	10 kg / m²
Weight per box	13 kg
Weight per box	28.6 lbs
CLASSIFICATION AND SAFETY	
Impact resistance (EN 17142)	>20N small ball, >1600 mm big ball
Thickness swelling (EN 17142)	<8% (6% typical)
Wear resistance (EN 17142)	AC6
CE Marked	Yes
Limited warranty (public environment)	10
Limited warranty (home environment)	Limited Lifetime Warranty
Formaldehyde emission (EN 717-1)	E1(<0.05ppm)
Level of use commercial (EN ISO 10874)	Class Very Heavy Commercial (Class 34)
Level of use domestic (EN ISO 10874)	Class Very Heavy Residential (Class 23)
Supports Underfloor Heating	Yes
Thermal conductivity (EN 12664)	0,16 W / mK
Thermal resistance (EN 12667)	R<0.10 (m2 x K)/W
Water resistance	High



Products

PRODUKTNAMN	TRÄSLAG	SURFACE FINISHING	STAINING	GRADING	S	M	L	XL	XXL
LUNA Dew Grey	Type of wood	Surface finishing	Staining	Grading					
NESO Eclipse Grey	Type of wood	Surface finishing	Staining	Grading					
TITAN Storm Grey	Type of wood	Surface finishing	Staining	Grading					