

Nadura Tiles

Specification

GENERAL

Type of floor	Nadura Tiles
Staining	Eclipse Grey Storm Grey Dew Grey
Pattern	Tile
Locking system	Välinge 5G Dry®
Core	HDF
Bevel	Decorative groove

DIMENSIONS

Width	280 mm
Length	582 mm
Thickness	10.5 mm
Thickness of wear layer	0.4 mm

PACKAGE

Quantity in box	8 pcs
m ² / box	1.3 m ²
m ² per pallet	70.4 m ²
Weight per m ²	10 kg / m ²
Weight per box	13 kg

CLASSIFICATION AND SAFETY

Thickness swelling (EN 17142)	<8% (6% typical)
CE Marked	Yes
Limited warranty (public environment)	10
Limited warranty (home environment)	Limited Lifetime Warranty
Formaldehyde emission (EN 717-1)	E1(<0.05ppm)
Impact resistance (EN 17142)	>20N small ball, >1600 mm big ball
Level of use commercial (EN ISO 10874)	Class Very Heavy Commercial (Class 34)
Level of use domestic (EN ISO 10874)	Class Very Heavy Residential (Class 23)
Supports Underfloor Heating	Yes
Thermal conductivity (EN 12664)	0,16 W / mK
Thermal resistance (EN 12667)	R<0.10 (m ² x K)/W
Water resistance	High
Wear resistance (EN 17142)	AC6



Products

PRODUKTNAMN	TRÄSLAG	SURFACE FINISHING	STAINING	GRADING	S	M	L	XL	XXL	CLASSIC	MODERN
NESO Eclipse Grey	Type of wood	Surface finishing	Eclipse Grey	Grading							
TITAN Storm Grey	Type of wood	Surface finishing	Storm Grey	Grading							
LUNA Dew Grey	Type of wood	Surface finishing	Dew Grey	Grading							