

Woodura Herringbone 3.0

Specification

GENERAL

Type of floor	Hardened wood
Type of wood	Oak
Grading	Select
Staining	Powder White Misty White Natural Terra Brown
Pattern	Herringbone
Surface finishing	Pro matt lacquer
Locking system	Välinge 5G Dry®
Core	Välinge Compositex® core
Bevel	Sharp edge

DIMENSIONS

	S	M	L	XL	XXL
Width					
Width (ISO 24337)					
Length					
Length (ISO 24337)					
Thickness					
Thickness (ASTM F387)					
Thickness of wear layer					

PACKAGE

	S	M	L	XL	XXL
Quantity in box					
m ² / box					
sq.ft per box					
m ² per pallet					
sq.ft per pallet					
Weight per box					
Weight per box					

CLASSIFICATION AND SAFETY

CE Marked	Yes
FSC	FSC Mix (FSC-C140725)
Limited warranty	20 years
Fire Resistance (EN 13501)	Cfl-S1 (hardly flammable)
Supports Underfloor Heating	Yes

woodura®

Bjelin Sweden AB | bjelin.com | support@bjelin.com | +46-771-101099

Copyright 2026 Bjelin Sweden AB. Weights and dimensions may have minor variations depending on external circumstances. Bjelin reserves the right to deviate from the weight and dimensions in this technical data sheet. Technologies mentioned may be subject to patent protection and invented by Välinge Innovation AB (www.valinge.se/patents). Use of trademarks herein owned by Bjelin Sweden AB or Välinge Innovation AB is under license.

Products

PRODUKTNAMN	TRÄSLAG	SURFACE FINISHING	STAINING	GRADING	S	M	L	XL	XXL
BODEN Classic 3.0	Oak	Pro matt lacquer	Powder White	Select					
BODEN Modern 3.0	Oak	Pro matt lacquer	Powder White	Select					
SIGTUNA Classic 3.0	Oak	Pro matt lacquer	Misty White	Select					
SIGTUNA Modern 3.0	Oak	Pro matt lacquer	Misty White	Select					
STOCKHOLM Classic 3.0	Oak	Pro matt lacquer	Natural	Select					
STOCKHOLM Modern 3.0	Oak	Pro matt lacquer	Natural	Select					
SANDVIKEN Classic 3.0	Oak	Pro matt lacquer	Terra Brown	Select					
SANDVIKEN Modern 3.0	Oak	Pro matt lacquer	Terra Brown	Select					